


## GS PREMIUM

NO	BATTERY TYPE	VOLT	CAPACITY 10 HR (Ah)	SIZE (mm)			PLATE PER CELL	TERMINAL
				L	W	H		
1	6N4-2A	6	4	70 (80)	70	95	5	
2	6N4-2A-2	6	4	70 (80)	70	95	5	
3	6N4-2A-4	6	4	70 (80)	70	95	5	
4	6N6-3B	6	6	98	56	110 (119)	7	
5	6N6-3B-1	6	6	98 (108)	56	110	7	
6	6N11-2D	6	11	149	69 (81)	99	17	
7	12N5-3B	12	4	120 (131)	60	130	5	
8	12N10-3B	12	10	135 (146)	90	145	7	
9	12N5,5-4B (MULTIPOLE)	12	5,5	135 (144)	60	130 (132)	7	
10	12N9-4B-1 (MULTIPOLE)	12	9	135 (146)	75	139 (143)	7	
11	12N10-3B (MULTIPOLE)	12	10	135 (146)	90	145 (152)	7	
12	GM2,5A-3C-2	12	2,5	80	70 (81)	105	3	
13	GM3-3B	12	3	98 (109)	56	110	5	
14	GM4-3B	12	4	120 (131)	70	92	7	
15	GM5Z-3B	12	5	120 (131)	60	130	7	
16	GM7B-4B	12	7	150 (160)	60	130	9	

## GS VALVE REGULATED LEAD ACID (GS VRLA)

NO	BATTERY TYPE	VOLT	CAPACITY 10 HR (Ah)	SIZE (mm)			PLATE PER CELL	TERMINAL
				L	W	H		
1	GTZ 4V	12	3	113	70	85	7	
2	GTZ 5S	12	3,5	113	70	85	7	
3	GTZ7S	12	5,5	113	70	105	7	

4	GT6A (GM5Z-3B)	12	5	120	60	130	7	
---	----------------	----	---	-----	----	-----	---	---