

Dry Charged Battery

GS Premium

GS Premium battery is popular among customers because it has proven to be dependable as well as suitable for any types of cars. GS Premium uses lead antimony alloy (Pb-sb) on both positive and negative plates.

A. GS Premium

BATTERY TYPE		CAPACITY		CCA	DIMENSION (mm)				LAY OUT	TERMINAL TYPE	BATTERY QTY PER PALLET	
OLD JIS	NEW JIS	5Hr (AH)	20Hr (AH)		L	W	H	TH			Large	Small
12N24R	26A19R	21	26	170	187	127	162	184	1	C	180	135
12N24L	26A19L	21	26	170	187	127	162	184	2	C	180	135
34B19R	34B19R	27	33	240	187	127	203	227	1	B	180	135
34B19L	34B19L	27	33	240	187	127	203	227	2	B	180	135
34B19RS	34B19RS	27	33	240	187	127	203	227	1	A	180	135
34B19LS	34B19LS	27	33	240	187	127	203	227	2	A	180	135
NS40	32B20R	26	32	225	197	129	203	227	1	B	168	126
NS40L	32B20L	26	32	225	197	129	203	227	2	B	168	126
NS40S	32B20RS	26	32	225	197	129	203	227	1	A	168	126
NS40LS	32B20LS	26	32	225	197	129	203	227	2	A	168	126
NS40Z	36B20R	28	35	260	197	129	203	227	1	B	168	126
NS40ZL	36B20L	28	35	260	197	129	203	227	2	B	168	126
NS40ZLS	36B20LS	28	35	260	197	129	203	227	2	A	168	126

(*) 20 HR capacity is based on calculation (approximately)

Strong Points GS Premium

- Strong, heavy duty, durable battery
- Reliable quality at economical price



A. GS Premium

BATTERY TYPE		CAPACITY		CCA (A)	DIMENSION (mm)				LAY OUT	TERMINAL TYPE	BATTERY QTY PER PALLET	
OLD JIS	NEW JIS	5Hr (AH)*	20Hr (AH)*		L	W	H	TH			Large	Small
NS40ZS	36B20RS	28	35	260	197	129	203	227	1	A	168	126
N40	32C24R	32	40	195	238	129	203	227	1	A	144	108
N40L	32C24L	32	40	195	238	129	203	227	2	A	144	108
NS60	46B24R	36	45	295	238	129	203	227	1	B	144	108
NS60L	46B24L	36	45	295	238	129	203	227	2	B	144	108
NS60S	46B24RS	36	45	295	238	129	203	227	1	A	144	108
NS60LS	46B24LS	36	45	295	238	129	203	227	2	A	144	108
55D23R	55D23R	48	60	320	232	173	204	225	1	A	112	84
55D23L	55D23L	48	60	320	232	173	204	225	2	A	112	84
75D23R	75D23R	52	65	465	232	173	204	225	1	A	112	84
75D23L	75D23L	52	65	465	232	173	204	225	2	A	112	84
N50	48D26R	40	50	250	260	173	204	225	1	A	96	72
N50L	48D26L	40	50	250	260	173	204	225	2	A	96	72
N50Z	55D26R	48	60	290	260	173	204	225	1	A	96	72
N50ZL	55D26L	48	60	290	260	173	204	225	2	A	96	72
NS70	65D26R	52	65	370	260	173	204	225	1	A	96	72
NS70L	65D26L	52	65	370	260	173	204	225	2	A	96	72
80D26R	80D26R	55	65	490	260	173	204	225	1	A	96	72
80D26L	80D26L	55	65	490	260	173	204	225	2	A	96	72
N70	65D31R	56	70	340	306	173	204	225	1	A	84	63
N70L	65D31L	56	70	340	306	173	204	225	2	A	84	63
N70Z	75D31R	60	75	380	306	173	204	225	1	A	84	63
N70ZL	75D31L	60	75	380	306	173	204	225	2	A	84	63
NX120-7R	95D31R	64	80	565	306	173	204	225	1	A	84	63
NX120-7L	95D31L	64	80	565	306	173	204	225	2	A	84	63
105D31R	105D31R	64	80	655	306	173	204	225	1	A	84	63
105D31L	105D31L	64	80	655	306	173	204	225	2	A	84	63
N100	95E41R	80	100	475	410	176	213	234	1	A	56	42
N100L	95E41L	80	100	475	410	176	213	234	2	A	56	42
NS120	115E41R	88	110	610	410	176	213	234	1	A	56	42
N120	115F51	96	120	575	505	182	213	257	3	A	-	36
N150	145G51	120	150	685	508	222	213	257	3	A	-	30
NS200	165G51	136	170	710	508	222	213	257	3	A	-	30
N200	190H52	160	200	765	521	278	220	270	3	A	-	24
555-65	555-65	-	55	255	246	175	190	190	1	A	96	72
555-59	555-59	-	55	255	246	175	190	190	2	A	96	72
566-38	566-38	-	66	300	299	175	190	190	2	A	84	63
566-18	566-18	-	80	300	306	175	190	190	2	A	84	63

(*) 20 HR capacity is based on calculation (approximately)