

MF Battery
GS Shield

GS Shield Battery uses lead calcium alloy (Pb-ca) material on both negative and positive plates to ensure that the rate of charge loss (self discharge) to beat its lowest level, making the engine easier to start up even in cold weather conditions or when the car is rarely used.

D. GS Shield (Maintenance Free)

BATTERY TYPE		CAPACITY		CCA (A)	DIMENSION (mm)				LAY OUT	TERMINAL TYPE	BATTERY QTY PER PALLET
OLD JIS	NEW JIS	5Hr (AH)	20Hr (AH)		L	W	H	TH			
34B19R	34B19R	27	34	240	187	127	203	227	1	B	135
34B19L	34B19L	27	34	240	187	127	203	227	2	B	135
34B19RS	34B19RS	27	34	240	187	127	203	227	1	A	135
34B19LS	34B19LS	27	34	240	187	127	203	227	2	A	135
NS40	32B20R	26	32	225	197	129	203	227	1	B	126
NS40L	32B20L	26	32	225	197	129	203	227	2	B	126
NS40S	32B20RS	26	32	225	197	129	203	227	1	A	126
NS40LS	32B20LS	26	32	225	197	129	203	227	2	A	126
NS40Z	36B20R	28	35	260	197	129	203	227	1	B	126
NS40ZL	36B20L	28	35	260	197	129	203	227	2	B	126
NS40ZLS	36B20LS	28	35	260	197	129	203	227	2	A	126
NS40ZS	36B20RS	28	35	260	197	129	203	227	1	A	126
NS60	46B24R	36	45	295	238	129	203	227	1	B	108
NS60L	46B24L	36	45	295	238	129	203	227	2	B	108
NS60S	46B24RS	36	45	295	238	129	203	227	1	A	108
NS60LS	46B24LS	36	45	295	238	129	203	227	2	A	108
55D23R	55D23R	48	60	320	232	173	204	225	1	A	84
55D23L	55D23L	48	60	320	232	173	204	225	2	A	84
N50	48D26R	40	50	250	260	173	204	225	1	A	72
N50L	48D26L	40	50	250	260	173	204	225	2	A	72
N50Z	55D26R	48	60	290	260	173	204	225	1	A	72
N50ZL	55D26L	48	60	290	260	173	204	225	2	A	72
NS70	65D26R	52	65	370	260	173	204	225	1	A	72
NS70L	65D26L	52	65	370	260	173	204	225	2	A	72
80D26R	80D26R	55	70	490	260	173	204	225	1	A	72
80D26L	80D26L	55	70	490	260	173	204	225	2	A	72
N70	65D31R	56	70	340	306	173	204	225	1	A	63
N70L	65D31L	56	70	340	306	173	204	225	2	A	63
N70Z	75D31R	60	75	380	306	173	204	225	1	A	63
N70ZL	75D31L	60	75	380	306	173	204	225	2	A	63
105D31R	105D31R	64	80	655	306	173	204	225	1	A	63
105D31L	105D31L	64	80	655	306	173	204	225	2	A	63
N100	115E41R	80	100	780	410	176	213	234	1	A	42
N100L	115E41L	80	100	780	410	176	213	234	2	A	42
N120/L	115F51	Under Development									
N150	145G51R	120	150	1.000	508	222	213	257	3	A	30
N150L	145G51L	120	150	1.000	508	222	213	257	4	A	30
N200/L	190H52	Under Development									

Strong Points GS SHIELD

- Premium Quality Material
- Good Packaging (Offset Design)
- No Need to Maintain The Battery (No Need Water Addition)

